



P.C.B LAYOUT

SPECIFICATIONS (技术参数)

Current Rating (额定电流): 3.0 Amps
 Contact Resistance (接触电阻): 30mΩ Max
 Insulator Resistance (绝缘电阻): 1000 MΩ min.
 Dielectric Withstanding (耐压值): AC 600V/minute
 Operating Temperature (工作温度): -40°C~+105°C



JSD FH XX X X X XX X X X XXX X

Brand 品牌
 Eyector Header 筒牛插座

Pitch 间距 (Unit:mm)
 10=1.00 12=1.27
 20=2.00 25=2.54

Ear height 耳朵高度 (Unit: mm)
 A=4.35
 B=8.00

Grooving direction 开槽方向
 0=In the middle (中间)
 1=On both sides of the (两边)

Add an insulator 添加绝缘体
 0=There is no (没有)
 1=There are (有)

Material Type 塑胶体材质
 0=PBT 3=PA9T
 1=PA46 4=LCP
 2=PA6T

Contact Plated 镀层
 0=Tin 锡 3=Gold 1.5U金 6=Gold 5U金
 1=Gold 0.8U金 4=Gold 2U金 7=Gold 10U金
 2=Gold 1.0U金 5=Gold 3U金 8=Gold 15U金

Mounting Style 安装方式
 S=Straight DIP Type 180度直插板
 R=Right Angle DIP Type 90度插板
 M=SMT vertical stick Type 立贴板

Number of contacts 触点总数
 Double row=06 to 140Pin

Locate the column (定位柱)
 0=No fixed 没有固定
 1=Have a fixed 有固定

Pin length 针的总长度

No. of Contacts	A	B	C
10	31.90	21.84	10.16
14	36.98	26.92	15.24
16	39.52	29.46	17.78
20	44.60	34.54	22.86
26	52.22	42.16	30.48
30	57.30	47.24	35.56
34	62.38	52.32	40.64
40	70.00	59.94	48.26
50	82.70	72.64	60.96
60	95.40	85.34	73.66
64	100.48	90.42	78.74

客户料号: 无

客户规格: 无

Units mm Scale

Tolerance Unless Otherwise Specified

Drawing By Date

2015年12月24日

Date 1 of 1 Title

Sheet Third Angle Projection

张火新

18824345453



深圳市精时代电子科技有限公司

官网: www.jsdconn.com

电话: 0755-33583386/33583396

传真: 0755-33583356

平面设计

2.54牛角180度直插高低卡位系列

注:

.X ~ ±0.30

.XX ~ ±0.30

.XXX ~ ±0.30

Angle ~ ±0.30

REV ECN.NO.

Drawing No. JSDEH25X0XXXXXXX-001 REV

F/Name B